

DV-AS-21 Wireless Presentation System









DESCRIPTION

The AirShare is a 2x1 Wireless Presentation System, which provides the perfect solution for smart workspaces such as boardrooms, classrooms, or any environment that benefits from content sharing. The AirShare provides simple connections via either a wireless or wired connection.

The wireless connection is standard 802.11n and supports Miracast and AirPlay. The AirShare also supports dual network capability allowing users to connect via a corporate or guest network providing the network security demanded in today's workplaces.

The AirShare features a built-in scaler that supports 1080P. With its auto switch capability the AirShare allows the active HDMI signal to switch to a wireless input, avoiding an additional control system or manual intervention.

The unit also features low-latency mouse control for additional source selection and annotation. A Win10 extended desktop for the presentation mode allows the presenter to view information on his/her own screen, and compliance with USB HID touch technology to work with White Boards and annotation.

SHARING WITHOUT BOUNDARIES





FEATURES

- Wireless-1080P@ ≤ 60Hz
- Auto-Password Update
- Real-time remote viewer
- Preview Windows
- Low-latency mouse control
- HDMI Auto-switch for HuddleVU Kits
- Segmented dual-network for guest internet
- WPA/WPA2 security
- Windows XP/Vista 7-10 and above,32 & 64 bit
- White board and annotation
- Distance of 35m from laptop to AirShare

FSR Inc.

244 Bergen Boulevard, Woodland Park, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207

Order Desk: 1-800-332-FSR1

Web: www.fsrinc.com · E-mail: sales@fsrinc.com





DV-AS-21 SPECIFICATIONS

Supported Formats	
Video Input Formats	1x Wireless, 1x HDMI
Format Compliance	WIFI 11n/ac
Video Output Formats	1x HDMI
Video Output Resolution	1920x1080@60Hz,1920x1200@60Hz
Format Compliance	HDMI1.4
Audio Input Formats	Digital Audio via HDMI or Stereo analog via 3.5mm mini jack
Audio Output Formats	HDMI: embedded digital audio
De-embedded analog stereo audio	20 k Ω impedance
Inputs Connectors	
Wireless Input	WIFI 11 n/ac
HDMI Input	1x HDMI 19-pin female connector
Stereo Analog Audio Input	1x 3.5mm PC audio female connector
Outputs Connectors	
HDMI Output	1x HDMI 19-pin female connector
Analog Audio Output	1x 3.5mm PC audio female connector
Features	
Number of window simultaneous on screen	1
Number of simultaneous connections	≤14
Data rate wireless	Up to 300Mbps, depending on the WIFI module of the laptop
Video Playback Frame Rate	20-30 FPS
Wireless transmission protocol	IEEE 802.11 a/g/n/ac
Frequency band	2.4 GHz and 5 GHz
Video Capacity	1080P @ ≤60Hz Airplay for IOS devices
	1080P @ ≤60Hz "WirelessMedia Lite" app
Remote Viewing	Mirroring remote view on mobile by app installed
Mobile Capability	Free IOS app, Free Android app
Encryption	AES WPA PSK, WPA2 PSK
Remote Mouse	Remote control moderator's PC
Control	
On-Screen Setting	Configuration Visual Button, by HID mouse, or remote control on APP
Ethernet	Telnet
Mechanical	
Dimensions (W x D x H)	5.5" x 3.74" x 0.63" (140mm x 95mm x 16mm)
Weight	0.4 lbs (200g)
Construction	1~2mm plastic with matte black finish
Environmental	
Operating Temperature	+32° to +104° F (0° to +40° C)
Storage Temperature	-4° to +140° F (-20° to +60° C)
Humidity (Storage / Operating)	20% to 90% (non-condensing)
Power	
DC Power	5V
Power Consumption	10W (max)
Accessories Included	
1x DC adapter with four plug-in, US, Europe, UK, Australia	







